


# Pacer

## Heat Tool Accessories

Heat tool accessories add extra capabilities to an already impressive line of products. These lightweight tools offer the ability to pinpoint heat, repair vinyl, solder, or repair solders as well as spot dry or shrink heat shrink. Each attachment you see here offers a unique advantage over the others. The entire point of these attachments is to give versatility and a wider range of functions. One of the best aspects is that you can quickly and easily remove an attachment and replace it with a new one in a matter of minutes. These are the tools that you'll find in repair shops, on job sites, and even in industrial settings.









Pacer is a Proud Member of:



## Heat Range

Although it varies with each tool, the heat range can exceed **1200°F/650°C**.

## Benefits

-  Large Temp. Ranges
-  Wide Variety of Uses
-  Built for Repeatability
-  Ideal for Field Usage
-  Long-Life Design
-  Simple to Use

## Uses & Applications


-  Production Facilities
-  Industrial Sites
-  Repair Shops
-  Personal Use
-  Marinas



## SELF-IGNITING, BUTANE POWERED SOLDERING IRON AND HEAT TOOL



**VUT100SI**



**VUT100SIK (KIT)**

- Light weight for easy handling & extended use
- Adjustable temperature up to 1200°F
- Use to pinpoint heat, remove surface mount components, repair vinyl, shrink heat tubing, solder & repair solders & spot dry
- Kit contains unit, solder tip, heat tip, shrink attachment, spanner & open end wrench, sponge & stand packed in a storage case
- Built-in fuel filter for consistent fuel ignition
- Built-in window indicates fuel level
- UL & GS/TUV Listed for user safety

### SPECIFICATIONS:

- Dimensions: 10.3" L (260 mm)
- Equivalent to Electric Iron: 20 to 80 Watt
- Net Weight: 5.5 oz. (100 g)
- Recommended Fuel: Master Ultratane® Butane
- Gas Tank Capacity: 1 fl. oz. (28 cc)
- Approx. Operating Time: 2hr.
- Approx. Heat Tip Temp.: 1202°F (650°C)
- Approx. Solder Tip Temp.: 482°F to 932°F (250°C to 500°C)

## ULTRATORCH ACCESSORIES

PART NUMBER	DESCRIPTION	PART NUMBER	DESCRIPTION
V70-01-01	1 mm Tapered Needle Soldering Tip	V70-01-12	Round head, High Powered 3 mm diameter
V70-01-02	3.3 mm Chisel Soldering Tip (Standard)	V70-01-14	Adaptor, 8.4 (4mm diameter x 0.7 mm pitch)
V70-01-03	2 mm Spade Soldering Tip	V70-01-16	5.7 O.D. Hot Knife Tip
V70-01-04	3 mm Spade Soldering Tip	V70-01-52	Heat Tip
V70-01-05	0.5 mm Tapered Needle Soldering Tip	V70-01-55	Heat Shrink Attachment
V70-01-06	2 mm Micro Spade Soldering Tip	V70-40U	Metal Storage Box
V70-01-08	2 mm Spade Soldering Tip 35 degree	V90-02	Protective Cap for VUT-100SI
V70-01-10	Offset tapered needle, 1 mm diameter	V80-04U	Replacement Burner
V70-01-11	8 mm High Powered Chisel Soldering Tip	VBUTANE	Butane 145 gm Canister



V70-01-01



V70-01-02



V70-01-03



V70-01-04



V70-01-05



V70-01-06



V70-01-08



V70-01-10



V70-01-11



V70-01-12



V70-01-14



V70-01-16



V70-01-52



V70-01-55



V70-40U



V90-02



V80-04U



VBUTANE